

SERIES Z SNAP-ACTION SWITCHES

CHARACTERISTICS:

Contact resistance: 15ohms max. (Initial)

Insulation resistance: 100Mohms min. (At 500VDC)

Dielectric strength: 1000 VAC 50/60Hz for 1 minute

Service life: Mechanically: 1,000,000 operations min.

Electrically: 100,000 operations min.



E88392

15A 125VAC or 250VAC

	<p>15A 125VAC or 250VAC 1/2A 125VDC 1/4A 250VDC 1/8HP 125VAC 1/4HP 250VAC</p>	<table border="1"> <thead> <tr> <th>Terminal</th> <th>Item No.</th> </tr> </thead> <tbody> <tr> <td>Solder</td> <td>Z15G1501</td> </tr> <tr> <td>Screw</td> <td>Z15G1701</td> </tr> <tr> <td>Operating Force max.</td> <td>70g</td> </tr> <tr> <td>Return Force min.</td> <td>14g</td> </tr> <tr> <td>Pretravel max. (PT)</td> <td>10 mm</td> </tr> <tr> <td>Overtravel min. (OT)</td> <td>5.6 mm</td> </tr> <tr> <td>Free Position max. (FP)</td> <td>28.2 mm</td> </tr> <tr> <td>Operating Position (OP)</td> <td>19 + 0.8mm</td> </tr> </tbody> </table>	Terminal	Item No.	Solder	Z15G1501	Screw	Z15G1701	Operating Force max.	70g	Return Force min.	14g	Pretravel max. (PT)	10 mm	Overtravel min. (OT)	5.6 mm	Free Position max. (FP)	28.2 mm	Operating Position (OP)	19 + 0.8mm
Terminal	Item No.																			
Solder	Z15G1501																			
Screw	Z15G1701																			
Operating Force max.	70g																			
Return Force min.	14g																			
Pretravel max. (PT)	10 mm																			
Overtravel min. (OT)	5.6 mm																			
Free Position max. (FP)	28.2 mm																			
Operating Position (OP)	19 + 0.8mm																			
	<p>15A 125VAC or 250VAC 1/2A 125VDC 1/4A 250VDC 1/8HP 125VAC 1/4HP 250VAC</p>	<table border="1"> <thead> <tr> <th>Terminal</th> <th>Item No.</th> </tr> </thead> <tbody> <tr> <td>Solder</td> <td>Z15G1502</td> </tr> <tr> <td>Screw</td> <td>Z15G1702</td> </tr> <tr> <td>Operating Force max.</td> <td>90g</td> </tr> <tr> <td>Return Force min.</td> <td>18g</td> </tr> <tr> <td>Pretravel max. (PT)</td> <td>8mm</td> </tr> <tr> <td>Overtravel min. (OT)</td> <td>4.2mm</td> </tr> <tr> <td>Free Position max. (FP)</td> <td>26.2mm</td> </tr> <tr> <td>Operating Position (OP)</td> <td>19 + 0.8mm</td> </tr> </tbody> </table>	Terminal	Item No.	Solder	Z15G1502	Screw	Z15G1702	Operating Force max.	90g	Return Force min.	18g	Pretravel max. (PT)	8mm	Overtravel min. (OT)	4.2mm	Free Position max. (FP)	26.2mm	Operating Position (OP)	19 + 0.8mm
Terminal	Item No.																			
Solder	Z15G1502																			
Screw	Z15G1702																			
Operating Force max.	90g																			
Return Force min.	18g																			
Pretravel max. (PT)	8mm																			
Overtravel min. (OT)	4.2mm																			
Free Position max. (FP)	26.2mm																			
Operating Position (OP)	19 + 0.8mm																			
	<p>15A 125VAC or 250VAC 1/2A 125VDC 1/4A 250VDC 1/8HP 125VAC 1/4HP 250VAC</p>	<table border="1"> <thead> <tr> <th>Terminal</th> <th>Item No.</th> </tr> </thead> <tbody> <tr> <td>Solder</td> <td>Z15G1503</td> </tr> <tr> <td>Screw</td> <td>Z15G1703</td> </tr> <tr> <td>Operating Force max.</td> <td>100g</td> </tr> <tr> <td>Return Force min.</td> <td>22g</td> </tr> <tr> <td>Pretravel max. (PT)</td> <td>7.1mm</td> </tr> <tr> <td>Overtravel min. (OT)</td> <td>4mm</td> </tr> <tr> <td>Free Position max. (FP)</td> <td>36.5mm</td> </tr> <tr> <td>Operating Position (OP)</td> <td>30.2 + 0.8mm</td> </tr> </tbody> </table>	Terminal	Item No.	Solder	Z15G1503	Screw	Z15G1703	Operating Force max.	100g	Return Force min.	22g	Pretravel max. (PT)	7.1mm	Overtravel min. (OT)	4mm	Free Position max. (FP)	36.5mm	Operating Position (OP)	30.2 + 0.8mm
Terminal	Item No.																			
Solder	Z15G1503																			
Screw	Z15G1703																			
Operating Force max.	100g																			
Return Force min.	22g																			
Pretravel max. (PT)	7.1mm																			
Overtravel min. (OT)	4mm																			
Free Position max. (FP)	36.5mm																			
Operating Position (OP)	30.2 + 0.8mm																			
	<p>15A 125VAC or 250VAC 1/2A 125VDC 1/4A 250VDC 1/8HP 125VAC 1/4HP 250VAC</p>	<table border="1"> <thead> <tr> <th>Terminal</th> <th>Item No.</th> </tr> </thead> <tbody> <tr> <td>Solder</td> <td>Z15G1504</td> </tr> <tr> <td>Screw</td> <td>Z15G1704</td> </tr> <tr> <td>Operating Force max.</td> <td>160g</td> </tr> <tr> <td>Return Force min.</td> <td>42g</td> </tr> <tr> <td>Pretravel max. (PT)</td> <td>2.7mm</td> </tr> <tr> <td>Overtravel min. (OT)</td> <td>2.4mm</td> </tr> <tr> <td>Free Position max. (FP)</td> <td>32.5mm</td> </tr> <tr> <td>Operating Position (OP)</td> <td>30.2 + 0.8mm</td> </tr> </tbody> </table>	Terminal	Item No.	Solder	Z15G1504	Screw	Z15G1704	Operating Force max.	160g	Return Force min.	42g	Pretravel max. (PT)	2.7mm	Overtravel min. (OT)	2.4mm	Free Position max. (FP)	32.5mm	Operating Position (OP)	30.2 + 0.8mm
Terminal	Item No.																			
Solder	Z15G1504																			
Screw	Z15G1704																			
Operating Force max.	160g																			
Return Force min.	42g																			
Pretravel max. (PT)	2.7mm																			
Overtravel min. (OT)	2.4mm																			
Free Position max. (FP)	32.5mm																			
Operating Position (OP)	30.2 + 0.8mm																			
	<p>15A 125VAC or 250VAC 1/2A 125VDC 1/4A 250VDC 1/8HP 125VAC 1/4HP 250VAC</p>	<table border="1"> <thead> <tr> <th>Terminal</th> <th>Item No.</th> </tr> </thead> <tbody> <tr> <td>Solder</td> <td>Z15G1544</td> </tr> <tr> <td>Screw</td> <td>Z15G1744</td> </tr> <tr> <td>Operating Force max.</td> <td>170g</td> </tr> <tr> <td>Return Force min.</td> <td>42g</td> </tr> <tr> <td>Pretravel max. (PT)</td> <td>2.7mm</td> </tr> <tr> <td>Overtravel min. (OT)</td> <td>2.4mm</td> </tr> <tr> <td>Free Position max. (FP)</td> <td>43.6mm</td> </tr> <tr> <td>Operating Position (OP)</td> <td>41.3 + 0.8mm</td> </tr> </tbody> </table>	Terminal	Item No.	Solder	Z15G1544	Screw	Z15G1744	Operating Force max.	170g	Return Force min.	42g	Pretravel max. (PT)	2.7mm	Overtravel min. (OT)	2.4mm	Free Position max. (FP)	43.6mm	Operating Position (OP)	41.3 + 0.8mm
Terminal	Item No.																			
Solder	Z15G1544																			
Screw	Z15G1744																			
Operating Force max.	170g																			
Return Force min.	42g																			
Pretravel max. (PT)	2.7mm																			
Overtravel min. (OT)	2.4mm																			
Free Position max. (FP)	43.6mm																			
Operating Position (OP)	41.3 + 0.8mm																			

SERIES Z SNAP-ACTION SWITCHES

CHARACTERISTICS:

Contact resistance: 15ohms max. (Initial)
 Insulation resistance: 100Mohms min. (At 500VDC)
 Dielectric strength: 1000 VAC 50/60Hz for 1 minute
 Service life: Mechanically: 1,000,000 operations min.
 Electrically: 100,000 operations min.



E88392
 15A 125VAC or 250VAC

ALL DIMENSIONS IN mm

	<p>WATERPROOF SEAL BOOT ON ACTUATOR</p> <p>15A 125VAC or 250VAC 1/2A 125VDC 1/4A 250VDC 1/8HP 125VAC 1/4HP 250VAC</p>	<table border="1"> <thead> <tr> <th>Terminal</th> <th>Item No.</th> </tr> </thead> <tbody> <tr> <td>Solder</td> <td>ZP15G1106</td> </tr> <tr> <td>Screw</td> <td>ZP15G1306</td> </tr> <tr> <td>Operating Force max.</td> <td>250-350g</td> </tr> <tr> <td>Releasing Force min.</td> <td>114g</td> </tr> <tr> <td>Pretravel max. (PT)</td> <td>0.4mm</td> </tr> <tr> <td>Overtravel min. (OT)</td> <td>1.6mm</td> </tr> <tr> <td>Operating position (OP)</td> <td>21.5 ± 0.5mm</td> </tr> </tbody> </table>	Terminal	Item No.	Solder	ZP15G1106	Screw	ZP15G1306	Operating Force max.	250-350g	Releasing Force min.	114g	Pretravel max. (PT)	0.4mm	Overtravel min. (OT)	1.6mm	Operating position (OP)	21.5 ± 0.5mm		
Terminal	Item No.																			
Solder	ZP15G1106																			
Screw	ZP15G1306																			
Operating Force max.	250-350g																			
Releasing Force min.	114g																			
Pretravel max. (PT)	0.4mm																			
Overtravel min. (OT)	1.6mm																			
Operating position (OP)	21.5 ± 0.5mm																			
	<p>WATERPROOF SEAL BOOT ON ACTUATOR</p> <p>15A 125VAC or 250VAC 1/2A 125VDC 1/4A 250VDC 1/8HP 125VAC 1/4HP 250VAC</p>	<table border="1"> <thead> <tr> <th>Terminal</th> <th>Item No.</th> </tr> </thead> <tbody> <tr> <td>Solder</td> <td>ZP15G1107</td> </tr> <tr> <td>Screw</td> <td>ZP15G1307</td> </tr> <tr> <td>Operating Force max.</td> <td>250-350g</td> </tr> <tr> <td>Releasing Force min.</td> <td>114g</td> </tr> <tr> <td>Pretravel max. (PT)</td> <td>0.4mm</td> </tr> <tr> <td>Overtravel min. (OT)</td> <td>5.5mm</td> </tr> <tr> <td>Operating position (OP)</td> <td>21.8 ± 0.8mm</td> </tr> </tbody> </table>	Terminal	Item No.	Solder	ZP15G1107	Screw	ZP15G1307	Operating Force max.	250-350g	Releasing Force min.	114g	Pretravel max. (PT)	0.4mm	Overtravel min. (OT)	5.5mm	Operating position (OP)	21.8 ± 0.8mm		
Terminal	Item No.																			
Solder	ZP15G1107																			
Screw	ZP15G1307																			
Operating Force max.	250-350g																			
Releasing Force min.	114g																			
Pretravel max. (PT)	0.4mm																			
Overtravel min. (OT)	5.5mm																			
Operating position (OP)	21.8 ± 0.8mm																			
	<p>15A 125VAC or 250VAC 1/2A 125VDC 1/4A 250VDC 1/8HP 125VAC 1/4HP 250VAC</p>	<table border="1"> <thead> <tr> <th>Terminal</th> <th>Item No.</th> </tr> </thead> <tbody> <tr> <td>Solder</td> <td>Z15G1106</td> </tr> <tr> <td>Screw</td> <td>Z15G1306</td> </tr> <tr> <td>Operating Force max.</td> <td>250-350g</td> </tr> <tr> <td>Releasing Force min.</td> <td>114g</td> </tr> <tr> <td>Pretravel max. (PT)</td> <td>0.4mm</td> </tr> <tr> <td>Overtravel min. (OT)</td> <td>1.6mm</td> </tr> <tr> <td>Operating position (OP)</td> <td>21.5 ± 0.5mm</td> </tr> </tbody> </table>	Terminal	Item No.	Solder	Z15G1106	Screw	Z15G1306	Operating Force max.	250-350g	Releasing Force min.	114g	Pretravel max. (PT)	0.4mm	Overtravel min. (OT)	1.6mm	Operating position (OP)	21.5 ± 0.5mm		
Terminal	Item No.																			
Solder	Z15G1106																			
Screw	Z15G1306																			
Operating Force max.	250-350g																			
Releasing Force min.	114g																			
Pretravel max. (PT)	0.4mm																			
Overtravel min. (OT)	1.6mm																			
Operating position (OP)	21.5 ± 0.5mm																			
	<p>15A 125VAC or 250VAC 1/2A 125VDC 1/4A 250VDC 1/8HP 125VAC 1/4HP 250VAC</p>	<table border="1"> <thead> <tr> <th>Terminal</th> <th>Item No.</th> </tr> </thead> <tbody> <tr> <td>Solder</td> <td>Z15G1505</td> </tr> <tr> <td>Screw</td> <td>Z15G1705</td> </tr> <tr> <td>Operating Force max.</td> <td>10g</td> </tr> <tr> <td>Return Force min.</td> <td>3g</td> </tr> <tr> <td>Pretravel max. (PT)</td> <td>20mm</td> </tr> <tr> <td>Overtravel min. (OT)</td> <td>5.6mm</td> </tr> <tr> <td>Free Position max. (FP)</td> <td>-</td> </tr> <tr> <td>Operating Position (OP)</td> <td>19 + 0.8mm</td> </tr> </tbody> </table>	Terminal	Item No.	Solder	Z15G1505	Screw	Z15G1705	Operating Force max.	10g	Return Force min.	3g	Pretravel max. (PT)	20mm	Overtravel min. (OT)	5.6mm	Free Position max. (FP)	-	Operating Position (OP)	19 + 0.8mm
Terminal	Item No.																			
Solder	Z15G1505																			
Screw	Z15G1705																			
Operating Force max.	10g																			
Return Force min.	3g																			
Pretravel max. (PT)	20mm																			
Overtravel min. (OT)	5.6mm																			
Free Position max. (FP)	-																			
Operating Position (OP)	19 + 0.8mm																			

CONSULT FACTORY FOR ADDITIONAL OPTIONS